

Bio-Boost

Septic system, Biocycle, Porta-loo
 & composting toilet booster & maintainer.



Product Overview

Our bio-enzymatic complex works to liquefy grease, fats, organic matter and other potential blockages and odours in septic systems, biocycle systems, portaloos, composting toilets, grease traps, drains & drain lines.

Billions of specially bred bacteria lie dormant in every litre of **Bio-Boost**, then spring to action when they contact waste & release enzymes that attack, digest & liquefy the matter.

Just like nature, but faster. With **Bio-Boost** your system can be free of odours and blockages without the use of hazardous chemicals & without the vile job of hand cleaning. Add **Bio-Boost** manually or with easy to install & inexpensive to operate automatic equipment.

Set the unit once & the computer memory will dispense just the right amount of product every day of the week, every week of the year.



Reduce, Reuse,
Recycle



Natural
Ingredients



Septic &
Biocycle Safe



Totally
Biodegradable



Earth Friendly
Technology



Australian
Owned & Made

Benefits

WORKS NATURES WAY, ONLY FASTER - Natural bacteria release enzymes that attack, liquefy & digest organic waste the safe & natural way that such matter has been eliminated from the earth for millions of years.

PREVENTS BLOCKED TRAPS AND LINES & eliminates the disgusting job of hand cleaning them.

AUTOMATIC DISPENSING - assures proper treatment as needed, without involvement of personnel.

WORKS FASTER than other bio-enzymatic digesters because it liquefies fatty, oily, greasy blockages faster. In fact, it is actually faster than widely advertised yet highly corrosive brands.

PAYS FOR ITSELF- by eliminating hand & "snake" cleaning & by avoiding fines & extra fees from local government.

STARTS A BIO-FILM on the inside surfaces of drain lines, that if maintained can prevent the accumulation of grease & future blockage.

REPLACES HAZARDOUS CAUSTICS - that can burn or disfigure personnel & damage drain lines.

ELIMINATES CHLORINATED SOLVENT that can contaminate the environment.

LEAVES AND ACTIVE BIO-FILM on the inside surface of traps & pipes to prevent accumulation of grease.

FORTIFIED with natural orange solvent to penetrate grease more quickly.

Bio-Boost saves you money by reducing the amount of pump outs. The bacteria will eat it!

50 BILLION ORGANISMS PER LITRE guaranteeing high enzyme producing bacteria counts.

TESTED & CERTIFIED by a qualified microbiologist to be free of salmonella & shigella bacteria.

BLEACH & CHLORINE RESISTANT bacteria strains allow Maintain to produce superior results under the most demanding conditions.

TEMPERATURE RESISTANT bacteria will not be harmed by temperature surges so common with washing equipment.

Bio-Boost Septic system, Biocycle, Porta-loo & composting toilet booster.

Bio-Boost is a complex of engineered micro organisms blended with natural solvents derived from citrus fruit.

Bio-Boost works nature's way but faster in biodegradation of organic waste in septic systems, biocycle systems, porta-loos, composting toilets, grease traps, drains & drain lines.

The safe-for-the-environment unique strains of enzyme producing bacteria build a bio-mass that will digest and liquefy potential blockages saving you money with less pump outs and less material pumped from your holding tank.

Uses

For cleaning & septic systems, biocycle systems, porta-loos, composting toilets, grease traps, drains & drain lines.

Directions

Because every system is different the bacteria may grow at varied rates. You can adjust the dose rates below to suite your needs. Start with the highest rate and slowly reduce either dose strength or frequency to make the product more economical. If your system is smelly Bio-Boost is best used after application of BioEnzymes OPEN BioEnzymatic Drain & Line Cleaner.

For problematic systems for best results first remove as much material from the holding tank as practical. If possible flush drain lines with hot water to remove build-up. Add Bio-Boost after hours or when least amount of water is running through the system. This will allow the bacteria time to bloom and will start the bio-film in all drain lines leading to the holding tank. Then use below rates for recently emptied systems.

If your system has just been emptied restart growth of biomass by adding approx. 1lt of Bio-Boost to about 5 litres of warm water, apply to all drain lines leading to system for 3 to 5 days. Follow with 300ml to 500ml undiluted Bio-Boost every few days or weekly. When odours stop and system is functioning more smoothly reduce the rate to 100ml every few days or 1 week or as required. For general use and maintenance apply 200ml to 300ml undiluted every week or every few weeks as required. Commercial system sizes and conditions vary greatly, please contact BioEnzymes for a tailored solution for your system.

PORTA LOO'S & COMPOSTING TOILETS

Add 50ml -100ml to enough water to suit system requirements to refill holding tank. Repeat after every clean. Use approx. 30ml undiluted daily to maintain system & reduce odours.

Specifications

Microorganisms per gallon.	100 billion
Number of bio-strains.	7
Type strains.	enzyme producing bacteria
Salmonella content.	none
pH concentrate.	7.0 +/- 1.0
Optimum pH matter treated.	5-12
Appearance.	turbid orange liquid
Odour of liquid.	orange peel
Odor counter-actant.	airicide
Grease penetrating additive.	d-limonene
Surfactant biodegradability.	rapid and complete



Reduce, Reuse,
Recycle



Natural
Ingredients



Septic &
Biocycle Safe



Totally
Biodegradable



Earth Friendly
Technology



Australian
Owned & Made